

JS006470175B1

(12) United States Patent Park et al.

(10) Patent No.: US 6,470,175 B1

(45) **Date of Patent:** Oct. 22, 2002

(54) FLIP-UP TYPE PORTABLE PHONE AND HINGE MECHANISM THEREOF

(75) Inventors: Sung-Sun Park; Kwang-Jin Bae, both of Kumi-shi (KR)

(73) Assignee: Samsung Electronics, Co., Ltd. (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/222,392

Dec. 29, 1997

(22) Filed: Dec. 29, 1998

(30) Foreign Application Priority Data

Aug.	18, 1998	(KK).		•••••	98-334/8
(51)	Int. Cl. ⁷				H04B 1/38
(52)	U.S. Cl.		455/90	; 455/575;	379/433.13
(58)	Field of	Search		455/9	0, 550, 575,

455/462; 379/428, 430, 433, 433.12, 433.13;

(KR) 97-76184

D14/137, 138

(56) References Cited

U.S. PATENT DOCUMENTS

5,752,204 A	*	5/1998	Epperson et al 455/575
5,809,403 A	*	9/1998	MacDonald, Jr. et al 455/90
5,896,575 A	*	4/1999	Higginbotham et al 455/575
5,960,357 A	*	9/1999	Kim 455/462

6,091,964	Α	*	7/2000	Frohlund	455/550
6,125,289	Α	*	9/2000	Lee	455/575
6 141 540	Α	*	10/2000	Richards et al	455/575

OTHER PUBLICATIONS

"Webster's II New Riverside University Dictionary", p. 321, 1988.

* cited by examiner

Primary Examiner—Nay Maung

(74) Attorney, Agent, or Firm—Dilworth & Barrese, LLP

(57) ABSTRACT

A flip-up type portable phone and a hinge mechanism for opening and closing a flip cover of such a flip-up type portable phone. A speaker is mounted in the interior of the flip cover, so that the space for occupying the speaker is eliminated from a phone body, thereby enabling the phone body to be compact. The hinge mechanism includes a pair of hinge assemblies adapted to open and close a flip cover and arranged at opposite sides of a liquid crystal display module disposed at the upper portion of the phone body, so that the flip cover can be opened by an upward pivotal movement thereof carried out about hinge shafts arranged at opposite sides of the LCD module. Accordingly, a microphone unit can be arranged at the lower end of the phone body. Moreover, the microphone unit can be arranged at an optional position on the lower end of the phone body. In accordance with the above arrangement, the LCD unit is always exposed.

25 Claims, 28 Drawing Sheets

